



Bewehrungstabelle 400
für Röckelein-Elementplatten, BSt 500 S(A)

Typ	Bewehrung längs (mm) Bewehrung quer1 (mm) Bewehrung quer2 (mm)	Abstand (cm) Abstand (cm) Abstand (cm)	Querschnitt längs (cm ² /m) Querschnitt quer (cm ² /m)	Gewicht (kg/m ²)
R401	6 6 6	16 50 50	1,77 1,13	2,28
R402	8 6 6	18 50 50	2,79 1,13	3,08
R403	8 6 6	15 50 50	3,35 1,13	3,52
R404	8 6 6	12 50 50	4,19 1,13	4,18
R405	10 6 6	15 50 50	5,24 1,13	5,00
R406	10 6 6	12 45 40	6,54 1,34	6,19
R407	12 6 6	15 35 40	7,54 1,52	7,11
R408	12 6 6	12 25 35	9,42 1,94	8,92
R409	14 8 6	15 40 35	10,26 2,07	9,68
R410	14 8 6	12 30 30	12,83 2,62	12,13
R411	14 8 6	10 25 25	15,39 3,14	14,55
R412	14 10 6	7,5 25 25	20,52 4,27	19,46
R413	14 12 6	6 25 25	25,66 5,66	24,59
R414	14 12 6	5,0 20 25	30,78 6,79	29,49

Kaspar Röckelein KG
Baustoffwerke - Baustoffgroßhandel
Hauptverwaltung
96199 Wachenroth, Tel. 09348 / 89 - 0

Wachenroth, den 12.04.2013; Dr.-Ing. Hu